

Three Piece Wall Mounted Basin/Bath Mixer





Product features:


- · Metal construction throughout
- Quarter turn handle action for precise flow control
- · Custom designed for lower range pressures
- Fixed spout to prevent accidental water damage
- · Adjustable to suit various thickness of wall

Packaged properties:

Box length (mm): 415 Box depth(mm): 95
Box width(mm): 180 Boxed weight (Kg): 2.36

Includes pop up waste?: No Additional comments:

Product dimensions:



• Product mounted where: Wall

• Recommended hole size: 28, 20, 28 mm


Overall Height / projection: 284 mm
Exit reach: 180-215 mm
Exit height: 70 mm
Base size: 55, 50, 55 mm

• Inlet centre distance(s): 220 mm

• Min. fitting depth required: 60 - 195 mmN/A mm

• Max. surface depth:

Product flow characteristics:



- Min / Max water pressure (bar): 0.50* / 5.00
- Part G max. mixed flow rate at 3 bar (I/m): 14.78
- Inlet connection type / length: Fixed / mm
- Inlet (plumbing connection) / outlet size: 1/2" F /
- Product flow characteristics: Single flow Non return valve(s) supplied or position: N/A
- Aerator type: Cache TT
- Control valve type: 1/2" QT CD (6-20)
- Includes output diverter?: No
- Inlet meshed particle filters included: N/A
- Shower hose type / length: N/A / N/A

Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

are instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build-up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives