Bayenne Single Lever C/W Integral Hendon Handspray AT3088 Product code: Product Finish: Century Copper EAN13 barcode: 5060344155359 **Product features:** Low lead brass construction • Single lever control for effortless single handed control • French provincial design aesthetic • Integral diverter from spout to sprayhead (spout flow stops when spray activated) • Leading design performance requiring higher pressures Additional information / Parts included: The installation of this product should respect requirement IRN R090. Triangular stabiliser Packaged properties: Box length (mm): 605 Box depth (mm): 85 Tap only weight (kg): 3.88 Box width (mm): 320 Units per outer: 5 Boxed weight (kg): 4.68 Product dimensions: • Overall Height / projection (mm): 327 • Exit reach (mm): 230 • Exit height (mm): 234 Centre distance(s): N/A • Base diameter(s) (mm): 66 Recommended hole diameter (mm): Ø 35 • Max. surface depth (mm): 60 • Spout diameter (mm): 20 • Spout aerator size: M24 BAYENNE SINGLE LEVER NTERGRAL HENDON abode Product flow characteristics: • Min / Max water pressure (bar): 1.50 / 5.5 • Recommended / Max water temperature: 46°C / 70°C • Part G - Mixed flow rate at 3 bar (litres / min): 9.32 Flow performance for model: Bayenne Single lever with integral spray • Control valve type: Single lever ceramic cartridge • Product flow characteristics: Single flow • Non-return/Check valve(s): Integral to H & C inlets and sprayhead • Aerator type: Neoperl honeycomb light blue • Accepts revolve / spray areator: No • Spout connection method: Locking collar • Tail pipe inlet / outlet size: 1/2" BSP Male / M10 • Inlet pipe type / length (mm): flexible stainless braided hose / 480 note 1: note 2: obode

Care instructions summary:

Clean the product regularly using a mild washing up liquid, do not use any other cleaners. Regular cleaning will prevent the build up of lime scale and dirt After cleaning rinse thoroughly with clean water to remove any cleaner residue Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives Warranty Summary (Full details available on request): .Materials and workmanship defects warranted for 5 years .Valves and working parts warranted for 5 years .Surface warranty defects warranted for 1 years .O-rings, hoses & gaskets warranted for 1 years

abode